



Using uM-FPU V2 with the PicBasic Pro Compiler®

Micromega Corporation


Introduction

The uM-FPU is a 32-bit floating point coprocessor that is easily interfaced with the Microchip PICmicro® family of microcontrollers, and programmed using the PicBasic Pro Compiler from microEngineering Labs Inc. The uM-FPU supports 32-bit floating point and 32-bit long integer operations and can be connected using either an I²C or SPI interface.

uM-FPU V2 Features

- 8-pin integrated circuit.
- I²C compatible interface up to 400 kHz
- SPI compatible interface up to 4 Mhz
- 32 byte instruction buffer
- Sixteen 32-bit general purpose registers for storing floating point or long integer values
- Five 32-bit temporary registers with support for nested calculations (i.e. parenthesis)
- Floating Point Operations
 - Set, Add, Subtract, Multiply, Divide
 - Sqrt, Log, Log10, Exp, Exp10, Power, Root
 - Sin, Cos, Tan, Asin, Acos, Atan, Atan2
 - Floor, Ceil, Round, Min, Max, Fraction
 - Negate, Abs, Inverse
 - Convert Radians to Degrees, Convert Degrees to Radians
 - Read, Compare, Status
- Long Integer Operations
 - Set, Add, Subtract, Multiply, Divide, Unsigned Divide
 - Increment, Decrement, Negate, Abs
 - And, Or, Xor, Not, Shift
 - Read 8-bit, 16-bit, and 32-bit
 - Compare, Unsigned Compare, Status
- Conversion Functions
 - Convert 8-bit and 16-bit integers to floating point
 - Convert 8-bit and 16-bit integers to long integer
 - Convert long integer to floating point
 - Convert floating point to long integer
 - Convert floating point to formatted ASCII
 - Convert long integer to formatted ASCII
 - Convert ASCII to floating point
 - Convert ASCII to long integer
- User Defined Functions can be stored in Flash memory
 - Conditional execution
 - Table lookup
 - Nth order polynomials

Pin Diagram and Pin Description



Pin	Name	Type	Description
1	CS	Input	Chip Select
2	SOUT	Output	SPI Output Busy/Ready
3	SCLK SCK	Input	SPI Clock I ² C Clock
4	VSS	Power	Ground
5	SIN SDA	Input In/Out	SPI Input I ² C Data
6	TSTOUT	Output	Test Output
7	TSTIN	Input	Test Input
8	VDD	Power	Supply Voltage


Connecting the uM-FPU to the Microchip PICmicro® using SPI

The uM-FPU can be connected using either a 2-wire or 3-wire. The 2-wire connection uses a clock signal and a bidirectional data signal and requires the program to change the input/output direction of the pin as required. The 3-wire connection uses a clock signal and separate data input and data output signals. Examples of the pin settings are as follows:


Pin	2-wire	3-wire
FpuClk	RC3	RC3
FpuIn	RC4	RC4
FpuOut	RC4	RC5

The settings of these pins can be changed to suit your application. By default, the uM-FPU chip is always selected, so the FpuClk and FpuIn/FpuOut pins should not be used for other connections as this will likely result in loss of synchronization between the PICmicro and the uM-FPU coprocessor.

3-wire SPI Connection



2-wire SPI Connection




If a 2-wire SPI interface is used, the SOUT and SIN pins should not be connected directly together, **they must be connected through a 1K resistor**. The microcontroller data pin is connected to the SIN pin. See the uM-FPU datasheet for further description of the SPI interface.

Connecting the uM-FPU to the PICmicro using I²C

The uM-FPU V2 can also be connected using an I²C interface. The default slave address for the uM-FPU is 0xC8 (LSB is the R/W bit, e.g. 0xC8 for write, 0xC9 for read). See the uM-FPU datasheet for further description of the I²C interface.

```
Fpu_SCL      I2C clock
Fpu_SDA      I2C data
Fpu_ID       $C8
define       I2C_HOLD 1
```

The settings for these pins can be changed to suit your application.



An Introduction to the uM-FPU

The following section provides an introduction to the uM-FPU using PicBasic Pro commands for all of the examples. For more detailed information about the uM-FPU, please refer to the following documents:

<i>uM-FPU V2 Datasheet</i>	functional description and hardware specifications
<i>uM-FPU V2 Instruction Set</i>	full description of each instruction

uM-FPU Registers

The uM-FPU contains sixteen 32-bit registers, numbered 0 through 15, which are used to store floating point or long integer values. Register 0 is reserved for use as a temporary register and is modified by some of the uM-FPU operations. Registers 1 through 15 are available for general use. Arithmetic operations are defined in terms of an A register and a B registers. Any of the 16 registers can be selected as the A or B register.

uM-FPU Registers

	0	32-bit Register
	1	32-bit Register
A →	2	32-bit Register
	3	32-bit Register
	4	32-bit Register
B →	5	32-bit Register
	6	32-bit Register
	7	32-bit Register
	8	32-bit Register
	9	32-bit Register
	10	32-bit Register
	11	32-bit Register
	12	32-bit Register
	13	32-bit Register
	14	32-bit Register
	15	32-bit Register

The FADD instruction adds two floating point values and is defined as $A = A + B$. To add the value in register 5 to the value in register 2, you would do the following:

- Select register 2 as the A register
- Select register 5 as the B register
- Send the FADD instruction ($A = A + B$)

We'll look at how to send these instructions to the uM-FPU in the next section.

Register 0 is a temporary register. If you want to use a value later in your program, store it in one of the registers 1 to 15. Several instructions load register 0 with a temporary value, and then select register 0 as the B register. As you will see shortly, this is very convenient because other instructions can use the value in register 0 immediately.

Sending Instructions to the uM-FPU

Appendix A contains a table that gives a summary of each uM-FPU instruction, with enough information to follow the examples in this document. For a detailed description of each instruction, refer to the document entitled *uM-FPU Instruction Set*.

To send instructions to the uM-FPU using an SPI interface, the SHIFTOUT command is used as follows:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [FADD+5]
```

To send instructions to the uM-FPU using an I²C interface, the I2CWRITE command is used as follows:

```
I2CWRITE Fpu_SDA, Fpu_SCL, Fpu_ID, 0, [FADD+5]
```

The part inside the square brackets specifies the instructions and data to send to the uM-FPU. The part before the square brackets is always the same, and depends on whether you are using an SPI or I²C interface. It specifies how the PICmicro will communicate with the uM-FPU. The `SHIFTOUT` command will be used for the examples in this document, but everything applies equally well to the `I2CWRITE` command. Note: There are some differences related to the handling of word variables. To send the word variable `cnt` with `SHIFTOUT` you specify the value as `cnt\16`. `I2CWRITE` will automatically send two bytes if `cnt` is defined as a word variable. An expression like `cnt*2` results in a word value and will cause two bytes to be sent by `I2CWRITE`. If a byte value is required, the expression should be calculated and assigned to a byte variable before using `I2CWRITE`. See the PicBasic Pro Compiler manual for more details.

All instructions start with an opcode that tells the uM-FPU which operation to perform. Some instructions require additional data or arguments, and some instructions return data. The most common instructions (the ones shown in the first half of the table in Appendix A), require a single byte for the opcode. For example:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [SQRT]
```

The instructions in the last half of the table, are extended opcodes, and require a two byte opcode. The first byte of extended opcodes is always `$FE`, defined as `XOP`. To use an extended opcode, you send the `XOP` byte first, followed by the extended opcode. For example:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, ATAN]
```

Some of the most commonly used instructions use the lower 4 bits of the opcode to select a register. This allows them to select a register and perform an operation at the same time. Opcodes that include a register value are defined with the register value equal to 0, so using the opcode by itself selects register 0. The following command selects register 0 as the B register then calculates $A = A + B$.

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [FADD]
```

To select a different register, you simply add the register value to the opcode. The following command selects register 5 as the B register then calculates $A = A + B$.

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [FADD+5]
```

Let's look at a more complete example. Earlier, we described the steps required to add the value in register 5 to the value in register 2. The command to perform that operation is as follows:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [SELECTA+2, FADD+5]
```

Description:

<code>SELECTA+2</code>	select register 2 as the A register
<code>FADD+5</code>	select register 5 as the B register and calculate $A = A + B$

It's a good idea to use constant definitions to provide meaningful names for the registers. This makes your program code easier to read and understand. The same example using constant definitions would be:

```
Total CON 2          'total amount (uM-FPU register)
Count  CON 5          'current count (uM-FPU register)
```

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [SELECTA+Total, FADD+Count]
```

Selecting the A register is such a common occurrence, it was defined as opcode `$0x`. The definition for `SELECTA` is `$00`, so `SELECTA+Total` is the same as just using `Total` by itself. Using this shortcut, the same example would now be:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Total, FADD+Count]
```

Tutorial Examples

Now that we've introduced some of the basic concepts of sending instructions to the uM-FPU, let's go through a tutorial example to get a better understanding of how it all ties together. This example will take a temperature reading from a DS1620 digital thermometer and convert it to Celsius and Fahrenheit.

Most of the data read from devices connected to the PICmicro will return some type of integer value. In this example, the interface routine for the DS1620 reads a 9-bit value and stores it in a Word variable called rawTemp. The value returned by the DS1620 is the temperature in units of 1/2 degrees Celsius. We need to load this value to the uM-FPU and convert it to floating point. The following command is used:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [DegC, LOADWORD, rawTemp\16, FSET]
```

Description:

DegreesC	select DegC as the A register
LOADWORD, rawTemp\16	load rawTemp to register 0, convert to floating point, select register 0 as the B register
FSET	DegC = register 0 (i.e. the floating point value of rawTemp)

The uM-FPU register DegC now contains the value read from the DS1620 (converted to floating point). Since the DS1620 works in units of 1/2 degree Celsius, DegC will be divided by 2 to get the degrees in Celsius.

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [LOADBYTE, 2, FDIV]
```

Description:

LOADBYTE, 2	load the value 2 to register 0, convert to floating point, select register 0 as the B register
FDIV	divide DegC by register 0 (i.e. divide by 2)

To get the degrees in Fahrenheit we will use the formula $F = C * 1.8 + 32$. Since 1.8 and 32 are constant values, they would normally be loaded once in the initialization section of your program and used later in the main program. The value 1.8 is loaded by using the ATOF (ASCII to float) instruction as follows:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [F1_8, ATOF, "1.8", 0, FSET]
```

Description:

F1.8	select F1_8 as the A register
ATOF, "1.8", 0	load the string 1.8 (note: the string must be zero terminated)
FSET	convert the string to floating point, store in register 0, select register 0 as the B register set F1_8 to the value in register 0 (i.e. 1.8)

The value 32 is loaded using the LOADBYTE instruction as follows:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [F32, LOADBYTE, 32, FSET]
```

Description:

F32	select F32 as the A register
LOADBYTE, 32	load the value 32 to register 0, convert to floating point, select register 0 as the B register
FSET	set F32 to the value in register 0 (i.e. 32.0)

Now using these constant values we calculate the degrees in Fahrenheit as follows:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [DegF, FSET+DegC, FMUL+F0_9, FADD+F32_0]
```

Description:

DegF	select DegF as the A register
FSET+DegC	set DegF = DegC
FMUL+F1_8	multiply DegF by 1.8
FADD+F32_0	add 32.0 to DegF

Now we print the results. There are support routines provided for printing floating point numbers. `Print_Float` prints an unformatted floating point value and displays up to eight digits of precision. `Print_FloatFormat` prints a formatted floating point number. We'll use `Print_FloatFormat` to display the results. The `format` variable is used to select the desired format. The tens digit is the total number of characters to display, and the ones digit is the number of digits after the decimal point. The DS1620 has a maximum temperature of 125° Celsius and one decimal point of precision, so we'll use a format of 51. Before calling the print routine the uM-FPU register is selected and the `format` variable is set. The following example prints the temperature in degrees Fahrenheit.

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [DegF]
format = 51
GOSUB Print_FloatFormat
```

Sample code for this tutorial and a wiring diagram for the DS1620 are shown at the end of this document. The file *demo1.bs2* is also included with the support software. There is a second file called *demo2.bs2* that extends this demo to include minimum and maximum temperature calculations. If you have a DS1620 you can wire up the circuit and try out the demos.

uM-FPU Support Software for the PicBasic Pro Compiler

Two include files contain all of the definitions and support code required for communicating with the uM-FPU.

```
umfpuV2-spi.bas    provides support for a 2-wire SPI connection
umfpuV2-i2c.bas   provides support for an I2C connection.
```

The main program should define the oscillator speed, debug port, uM-FPU pins and the uM-FPU include file as follows:

```
'----- PIC oscillator speed -----
define      OSC 20                      'specify the speed of the oscillator
OSC_SPEED   con 20                      'define PicBasic constant

'----- debug definitions -----
define      DEBUG_REG  PORTC
define      DEBUG_BIT  6
define      DEBUG_BAUD 9600
define      DEBUG_MODE 0

'----- uM-FPU pin definitions -----
FpuClk      var      PORTC.3
FpuIn       var      PORTC.4
FpuOut      var      PORTC.4

include     "umfpuV2-spi.bas"           'include the uM-FPU support routines
```

The include files contain the following:

- opcode definitions for all uM-FPU instructions
- variable definitions for the Word variable used by the support routines
- the support routines described below:

Fpu_Reset

To ensure that the PICmicro and the uM-FPU coprocessor are synchronized, a reset call must be done at the start of every program. The `Fpu_Reset` routine resets the uM-FPU, confirms communications, and sets the `fpu_status` variable to 1 if successful, or 0 if the reset failed.

Fpu_Wait

The uM-FPU must have completed all calculations and be ready to return the data before sending an instruction that reads data from the uM-FPU. The `Fpu_Wait` routine checks the status of the uM-FPU and waits until it is ready. The

print routines check the ready status, so it isn't necessary to call `Fpu_Wait` before calling a print routine. If your program reads directly from the uM-FPU using the `SHIFTIN` or `I2CREAD` commands, a call to `Fpu_Wait` must be made prior to sending the read instruction. An example of reading a byte value is as follows:

```
GOSUB Fpu_wait
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, READBYTE]
SHIFTIN FpuOut, FpuClk, MSBPRES, [dataByte]
```

Description:

- wait for the uM-FPU to be ready
- send the `READBYTE` instruction
- read a byte value and store it in the variable `dataByte`

The uM-FPU V2 has a 32 byte instruction buffer. In most cases, data will be read back before 32 bytes have been sent to the uM-FPU. If a long calculation is done that requires more than 32 bytes to be sent to the uM-FPU, an `Fpu_Wait` call should be made at least every 32 bytes to ensure that the instruction buffer doesn't overflow.

Fpu_ReadDelay

After a read instruction is sent, and before the first data is read, a setup delay is required to ensure that the uM-FPU is ready to send data. The `Fpu_ReadDelay` routine provides the required read setup delay. For read instructions that return multiple bytes, the `Fpu_ReadDelay` call is only required before the first byte.

Fpu_ReadStatus

This routine reads the status byte from the uM-FPU and returns the value in the variable `fpu_status`. An instruction that returns the status (e.g. `FSTATUS`, `FCOMPARE`, etc.) must have been sent immediately prior to calling the `Fpu_ReadStatus` routine.

Print_Version

Prints the uM-FPU version string to the PC screen using the `DEBUG` command.

Print_Float

The value in register A is displayed on the PC screen as a floating point value using the `DEBUG` command. Up to eight significant digits will be displayed if required. Very large or very small numbers are displayed in exponential notation. The length of the displayed value is variable and can be from 3 to 12 characters in length. The special cases of NaN (Not a Number), +Infinity, -Infinity, and -0.0 are handled. Examples of the display format are as follows:

1.0	NaN	0.0
1.5e20	Infinity	-0.0
3.1415927	-Infinity	1.0
-52.333334	-3.5e-5	0.01

Print_FloatFormat

The value in register A is displayed on the PC screen as a formatted floating point value using the `DEBUG` command. The `format` variable is used to specify the desired format. The tens digit specifies the total number of characters to display and the ones digit specifies the number of digits after the decimal point. If the value is too large for the format specified, then asterisks will be displayed. If the number of digits after the decimal points is zero, no decimal point will be displayed. Examples of the display format are as follows:

Value in A register	format	Display format
123.567	61 (6.1)	123.6
123.567	62 (6.2)	123.57
123.567	42 (4.2)	*.*
0.9999	20 (2.0)	1
0.9999	31 (3.1)	1.0

Print_Long

The value in register A is displayed on the PC screen as a signed long integer using the `DEBUG` command. The displayed value can range from 1 to 11 characters in length. Examples of the display format are as follows:

```

1
500000
-3598390

```

Print_LongFormat

The value in register A is displayed on the PC screen as a formatted long integer using the DEBUG command. The `format` variable is used to specify the desired format. A value between 0 and 15 specifies the width of the display field for a signed long integer. The number is displayed right justified. If 100 is added to the format value the value is displayed as an unsigned long integer. If the value is larger than the specified width, asterisks will be displayed. If the width is specified as zero, the length will be variable. Examples of the display format are as follows:

Value in register A	format	Display format
-1	10 (signed 10)	-1
-1	110 (unsigned 10)	4294967295
-1	4 (signed 4)	-1
-1	104 (unsigned 4)	****
0	4 (signed 4)	0
0	0 (unformatted)	0
1000	6 (signed 6)	1000

Loading Data Values to the uM-FPU

There are several instructions for loading integer values to the uM-FPU. These instructions take an integer value as an argument, stores the value in register 0, converts it to floating point, and selects register 0 as the B register. This allows the loaded value to be used immediately by the next instruction.

LOADBYTE	Load 8-bit signed integer and convert to floating point
LOADUBYTE	Load 8-bit unsigned integer and convert to floating point
LOADWORD	Load 16-bit signed integer and convert to floating point
LOADUWORD	Load 16-bit unsigned integer and convert to floating point

For example, to calculate $\text{Result} = \text{Result} + 20.0$

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Result, LOADBYTE, 20, FADD]
```

Description:

Result	select Result as the A register
LOADBYTE, 20	load the value 20 to register 0, convert to floating point, select register 0 as the B register
FADD	add register 0 to Result

The following instructions take integer value as an argument, stores the value in register 0, converts it to a long integer, and selects register 0 as the B register.

LONGBYTE	Load 8-bit signed integer and convert to 32-bit long signed integer
LONGUBYTE	Load 8-bit unsigned integer and convert to 32-bit long unsigned integer
LONGWORD	Load 16-bit signed integer and convert to 32-bit long signed integer
LONGUWORD	Load 16-bit unsigned integer and convert to 32-bit long unsigned integer

For example, to calculate $\text{Total} = \text{Total} / 100$

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Total, XOP, LONGBYTE, 100, LDIV]
```

Description:

Total	select Total as the A register
XOP, LONGBYTE, 100	load the value 100 to register 0, convert to long integer, select register 0 as the B register
LDIV	divide Total by register 0

There are several instructions for loading commonly used constants. These instructions load the constant value to register 0, and select register 0 as the B register.

LOADZERO	Load the floating point value 0.0 (or long integer 0)
----------	---

LOADONE	Load the floating point value 1.0
LOADE	Load the floating point value of e (2.7182818)
LOADPI	Load the floating point value of pi (3.1415927)

For example, to set Result = 0.0

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Result, XOP, LOADZERO, FSET]
```

Description:

Result	select Result as the A register
XOP, LOADZERO	load 0.0 the register 0 and selects register 0 as the B register
FSET	set Result to the value in register 0 (Result = 0.0)

There are two instructions for loading 32-bit floating point values to a specified register. This is one of the more efficient ways to load floating point constants, but requires knowledge of the internal representation for floating point numbers (see Appendix B). A handy utility program called *uM-FPU Converter* is available to convert between floating point strings and 32-bit hexadecimal values.

WRITEA	Write 32-bit floating point value to specified register
WRITAB	Write 32-bit floating point value to specified register

For example, to set Angle = 20.0 (the floating point representation for 20.0 is \$41A00000)

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [WRITEA+Angle, $41,$A0,$00,$00]
```

Description:

WRITEA+Angle	select Angle as the A register and load 32-bit value
\$41, \$A0, \$00, \$00	the value \$41A00000 is loaded to Angle

There are two instructions for loading 32-bit long integer values to a specified register.

LWRITEA	Write 32-bit long integer value to specified register
LWRITAB	Write 32-bit long integer value to specified register

For example, to set Total = 500000

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, LWRITEA+Total, $00,$07,$A1,$20]
```

Description:

XOP, LWRITEA+Total	select Total as the A register and load 32-bit value
\$00, \$07, \$A1, \$20	the value \$0007A120 is loaded to Total

There are two instructions for converting strings to floating point or long integer values.

ATOF	Load ASCII string and convert to floating point
ATOL	Load ASCII string and convert to long integer

For example, to set Angle = 1.5885

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Angle, ATOF, "1.5885", 0, FSET]
```

Description:

Angle	select Angle as the A register
ATOF, "1.5885", 0	load the string 1.5885 to the uM-FPU and convert to floating point (note the string must be zero terminated) the value is stored in register 0 and register 0 is selected as the B register
FSET	set Angle to the value in register 0

For example, to set Total = 500000

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Total, ATOL, "5000000", 0, FSET]
```

Description:

Total	select Total as the A register
ATOL, "5000000", 0	load the string 500000 to the uM-FPU and convert to floating point (note the string must be zero terminated) the value is stored in register 0 and register 0 is selected as the B register
LSET	set Total to the value in register 0

The fastest operations occur when the uM-FPU registers are already loaded with values. In time critical portions of code floating point constants should be loaded beforehand to maximize the processing speed in the critical section. With 15 registers available for storage on the uM-FPU, it is often possible to preload all of the required constants. In non-critical sections of code, data and constants can be loaded as required.

Reading Data Values from the uM-FPU

There are two instruction for reading 32-bit floating point values from the uM-FPU.

READFLOAT	Reads a 32-bit floating point value from the A register.
FREAD	Reads a 32-bit floating point value from the specified register.

The following commands read the floating point value from the A register

```
GOSUB Fpu_wait
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, READFLOAT]
SHIFTIN FpuOut, FpuClk, MSBPRES, [byte0, byte1, byte2, byte3]
```

Description:

- wait for the uM-FPU to be ready
- send the READFLOAT instruction
- read the 32-bit value and store it in variables byte0, byte1, byte2, byte3

There are four instruction for reading integer values from the uM-FPU.

READBYTE	Reads the lower 8 bits of the value in the A register.
READWORD	Reads the lower 16 bits of the value in the A register.
READLONG	Reads a 32-bit long integer value from the A register.
LREAD	Reads a 32-bit long integer value from the specified register.

The following commands read the lower 8 bits from the A register

```
GOSUB Fpu_wait
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, READBYTE]
SHIFTIN FpuOut, FpuClk, MSBPRES, [dataByte]
```

Description:

- wait for the uM-FPU to be ready
- send the READBYTE instruction
- read a byte value and store it in the variable dataByte

Comparing and Testing Floating Point Values

A floating point value can be zero, positive, negative, infinite, or Not a Number (which occurs if an invalid operation is performed on a floating point value). To check the status of a floating point number the FSTATUS instruction is sent, and the returned byte is stored in the `fpu_status` variable. A bit definition is provided for each status bit in the `status` variable. They are as follows:

<code>status_Zero</code>	Zero status bit (0-not zero, 1-zero)
<code>status_Sign</code>	Sign status bit (0-positive, 1-negative)
<code>status_NaN</code>	Not a Number status bit (0-valid number, 1-NaN)
<code>status_Inf</code>	Infinity status bit (0-not infinite, 1-infinite)

For example:

```
GOSUB Fpu_Wait
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [FSTATUS]
GOSUB Fpu_ReadStatus
IF (status_Sign = 1) THEN DEBUG "Result is negative"
IF (status_Zero = 1) THEN DEBUG "Result is zero"
```

The FCOMPARE instruction is used to compare two floating point values. The status bits are set for the results of the operation $A - B$ (The selected A and B registers are not modified). For example, the following commands compare the values in registers Value1 and Value2.

```
GOSUB Fpu_Wait
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Value1, SELECTB+Value2, FCOMPARE]
GOSUB Fpu_ReadStatus

IF (status_Zero = 1) THEN
  DEBUG "Value1 = Value2"
ELSEIF (status_Sign = 1) THEN
  DEBUG "Value1 < Value2"
ELSE
  DEBUG "Value1 > Value2"
ENDIF
```

Comparing and Testing Long Integer Values

A long integer value can be zero, positive, or negative. To check the status of a long integer number the LSTATUS instruction is sent, and the returned byte is stored in the `status` variable. A bit definition is provided for each status bit in the `status` variable. They are as follows:

<code>status_Zero</code>	Zero status bit (0-not zero, 1-zero)
<code>status_Sign</code>	Sign status bit (0-positive, 1-negative)

For example:

```
GOSUB Fpu_wait
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, LSTATUS]
GOSUB Fpu_ReadStatus
IF (status_Sign = 1) THEN DEBUG "Result is negative"
IF (status_Zero = 1) THEN DEBUG "Result is zero"
```

The LCOMPARE and LUCOMPARE instructions are used to compare two long integer values. The status bits are set for the results of the operation $A - B$ (The selected A and B registers are not modified). LCOMPARE does a signed compare and LUCOMPARE does an unsigned compare. For example, the following commands compare the values in registers Value1 and Value2.

```
GOSUB Fpu_wait
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Value1, SELECTB+Value2, XOP, LCOMPARE]
GOSUB Fpu_ReadStatus
IF (status_Zero = 1) THEN
  DEBUG "Value1 = Value2"
ELSEIF (status_Sign = 1) THEN
  DEBUG "Value1 < Value2"
ELSE
  DEBUG "Value1 > Value2"
```

Left and Right Parenthesis

Mathematical equations are often expressed with parenthesis to define the order of operations. For example $Y = (X-1) / (X+1)$. The LEFT and RIGHT parenthesis instructions provide a convenient means of allocating temporary values and changing the order of operations.

When a LEFT parenthesis instruction is sent, the current selection for the A register is saved and the A register is set to reference a temporary register. Operations can now be performed as normal with the temporary register selected as the A register. When a RIGHT parenthesis instruction is sent, the current value of the A register is copied to register 0, register 0 is selected as the B register, and the previous A register selection is restored. The value in register 0 can be used immediately in subsequent operations. Parenthesis can be nested for up to five levels. In most situations, the user's code does not need to select the A register inside parentheses since it is selected automatically by the LEFT and RIGHT parentheses instructions.

In the following example the equation $Z = \sqrt{X^2 + Y^2}$ is calculated. Note that the original values of X and Y are retained.

```
Xvalue CON 1          'X value (uM-FPU register 1)
Yvalue CON 2          'Y value (uM-FPU register 2)
Zvalue CON 3          'Z value (uM-FPU register 3)

SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Zvalue, FSET+Xvalue, FMUL+Xvalue]
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, LEFT, FSET+Yvalue, FMUL+Yvalue]
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, RIGHT, FADD, FSQRT]
```

Description:

Zvalue	select Zvalue as the A register
FSET+Xvalue	Zvalue = Xvalue
FMUL+Xvalue	Zvalue = Zvalue * Xvalue (i.e. X**2)
XOP, LEFT	save current A register selection, select temporary register as A register (temp)
FSET+Yvalue	temp = Yvalue
FMUL+Yvalue	temp = temp * Yvalue (i.e. Y**2)
XOP, RIGHT	store temp to register 0, select Zvalue as A register (previously saved selection)
FADD	add register 0 to Zvalue (i.e. X**2 + Y**2)
SQRT	take the square root of Zvalue

The following example shows $Y = 10 / (X + 1)$:

```
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [Yvalue, LOADBYTE, 10, FSET]
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, LEFT, FSET+Xvalue, XOP, LOADONE, FADD]
SHIFTOUT FpuOut, FpuClk, MSBFIRST, [XOP, RIGHT, FDIV]
```

Description:

Yvalue	select Yvalue as the A register
LOADBYTE, 10	load the value 10 to register 0, convert to floating point, select register 0 as the B register
FSET	Yvalue = 10.0
XOP, LEFT	save current A register selection, select temporary register as A register (temp)
FSET+Xvalue	temp = Xvalue
XOP, LOADONE	load 1.0 to register 0 and select register 0 as the B register
FADD	temp = temp + 1 (i.e. X+1)
XOP, RIGHT	store temp to register 0, select Yvalue as A register (previously saved selection)
FDIV	divide Yvalue by the value in register 0


Further Information

The following documents are also available:

uM-FPU V2 Datasheet	provides hardware details and specifications
uM-FPU V2 Instruction Reference	provides detailed descriptions of each instruction

Check the Micromega website at www.micromegacorp.com for up-to-date information.

DS1620 Connections for Demo 1



Sample Code for Tutorial (Demo1-spi.bas)

```
' This program demonstrates the use of the uM-FPU V2 floating point coprocessor
' with the PicBasic Pro compiler using a SPI interface. It takes temperature
' readings from a DS1620 digital thermometer, converts them to floating point
' and displays them in degrees Celsius and degrees Fahrenheit.
```

```
'----- PIC oscillator speed -----
define      OSC 20                'specify the speed of the oscillator
OSC_SPEED  con 20                'define PicBasic constant
```

```
'----- debug definitions -----
define      DEBUG_REG  PORTC
define      DEBUG_BIT  6
define      DEBUG_BAUD 9600
define      DEBUG_MODE 0
```

```
'----- uM-FPU pin definitions -----
FpuClk      var  PORTC.3
FpuIn       var  PORTC.4
FpuOut      var  PORTC.4
```

```
include     "umfpuV2-spi.bas"      'include the uM-FPU support routines
```

```
'----- DS1620 pin definitions -----
DS_RST      var  PORTA.0          'DS1620 reset/enable
DS_CLK      var  PORTA.1          'DS1620 clock
DS_DATA     var  PORTA.2          'DS1620 data
```

```
LSBFIRST    con  0                'shiftout mode
LSBPRES     con  1                'shiftin mode
```

```
'----- uM-FPU register definitions -----
DegC        con  1                'degrees Celsius
DegF        con  2                'degrees Fahrenheit
F1_8        con  3                'constant 1.8
F32         con  4                'constant 32.0
```

```
'----- variables -----
```

```

rawTemp      var          word          'raw temperature reading

'=====
'----- initialization -----
'=====

Reset:
  DEBUG 13, 10, 13, 10, "Demo 1: "

  GOSUB Fpu_Reset              'initialize uM-FPU
  IF fpu_status <> SyncChar THEN
    DEBUG "uM-FPU not detected."
  END
  ELSE
    GOSUB Print_Version        'display version string
  ENDIF
  DEBUG 13, 10, "-----"

  GOSUB Init_DS1620            'initialize DS1620

                                'load floating point constants
  SHIFTOUT FpuOut, FpuClk, MSBFIRST, [F1_8, ATOF, "1.8", 0, FSET]
  SHIFTOUT FpuOut, FpuClk, MSBFIRST, [F32, LOADBYTE, 32, FSET]

'=====
'----- main routine -----
'=====

Main:
  GOSUB Read_DS1620            'get temperature reading from DS1620
  DEBUG 13, 10, 13, 10, "Raw Temp: ", IHEX4 rawTemp

                                'send rawTemp to uM-FPU
                                'convert to floating point
                                'store in register
  SHIFTOUT FpuOut, FpuClk, MSBFIRST, [DegC, LOADWORD, rawTemp\16, FSET]

                                'divide by 2 to get degrees Celsius
  SHIFTOUT FpuOut, FpuClk, MSBFIRST, [LOADBYTE, 2, FDIV]

                                'degF = degC * 1.8 + 32
  SHIFTOUT FpuOut, FpuClk, MSBFIRST, [DegF, FSET+DegC, FMUL+F1_8, FADD+F32]

  DEBUG 13, 10, "Degrees C: "  'display degrees Celsius
  SHIFTOUT FpuOut, FpuClk, MSBFIRST, [DegC]
  format = 51
  GOSUB Print_FloatFormat

  DEBUG 13, 10, "Degrees F: "  'display degrees Fahrenheit
  SHIFTOUT FpuOut, FpuClk, MSBFIRST, [DegF]
  format = 51
  GOSUB Print_FloatFormat

  PAUSE 2000                    'delay, then get the next reading
  GOTO Main
  END

'----- Init_DS1620 -----

Init_DS1620:
  ADCON1 = 6                    'configure A0-A3 for digital I/O
  LOW DS_RST                    'initialize pin states
  HIGH DS_CLK
  PAUSE 100

```

```

HIGH DS_RST                'configure for CPU control
SHIFTOUT DS_DATA, DS_CLK, LSBFIRST, [$0C, $02]
LOW DS_RST
PAUSE 100

HIGH DS_RST                'start temperature conversions
SHIFTOUT DS_DATA, DS_CLK, LSBFIRST, [$EE]
LOW DS_RST
PAUSE 1000                'wait for first conversion
RETURN

'----- Read_DS1620 -----

Read_DS1620:
HIGH DS_RST                'read temperature value
SHIFTOUT DS_DATA, DS_CLK, LSBFIRST, [$AA]
SHIFTOIN DS_DATA, DS_CLK, LSBPRE, [rawTemp\9]
LOW DS_RST                'extend the sign bit
IF rawTemp.BIT8 = 1 THEN rawTemp.HIGHBYTE = $FF
RETURN

```

Appendix A

uM-FPU V2 Instruction Summary

Opcode Name	Data Type	Opcode	Arguments	Returns	B Reg	Description
SELECTA		0x				Select A register
SELECTB		1x			x	Select B register
FWRITEA	Float	2x	yyyy zzzz			Write register and select A
FWRITEB	Float	3x	yyyy zzzz		x	Write register and select B
FREAD	Float	4x		yyyy zzzz		Read register
FSET/LSET	Either	5x				A = B
FADD	Float	6x			x	A = A + B
FSUB	Float	7x			x	A = A - B
FMUL	Float	8x			x	A = A * B
FDIV	Float	9x			x	A = A / B
LADD	Long	Ax			x	A = A + B
LSUB	Long	Bx			x	A = A - B
LMUL	Long	Cx			x	A = A * B
LDIV	Long	Dx			x	A = A / B Remainder stored in register 0
SQRT	Float	E0				A = sqrt(A)
LOG	Float	E1				A = ln(A)
LOG10	Float	E2				A = log(A)
EXP	Float	E3				A = e ** A
EXP10	Float	E4				A = 10 ** A
SIN	Float	E5				A = sin(A) radians
COS	Float	E6				A = cos(A) radians
TAN	Float	E7				A = tan(A) radians
FLOOR	Float	E8				A = nearest integer <= A
CEIL	Float	E9				A = nearest integer >= A
ROUND	Float	EA				A = nearest integer to A
NEGATE	Float	EB				A = -A
ABS	Float	EC				A = A
INVERSE	Float	ED				A = 1 / A
DEGREES	Float	EE				Convert radians to degrees A = A / (PI / 180)
RADIANS	Float	EF				Convert degrees to radians A = A * (PI / 180)
SYNC		F0		5C		Synchronization
FLOAT	Long	F1			0	Copy A to register 0 Convert long to float
FIX	Float	F2			0	Copy A to register 0 Convert float to long
FCOMPARE	Float	F3		ss		Compare A and B (floating point)
LOADBYTE	Float	F4	bb		0	Write signed byte to register 0 Convert to float
LOADUBYTE	Float	F5	bb		0	Write unsigned byte to register 0 Convert to float
LOADWORD	Float	F6	www		0	Write signed word to register 0 Convert to float
LOADUWORD	Float	F7	www		0	Write unsigned word to register 0 Convert to float
READSTR		F8		aa ... 00		Read zero terminated string from string buffer

ATOF	Float	F9	aa ... 00		0	Convert ASCII to float Store in A
FTOA	Float	FA	ff			Convert float to ASCII Store in string buffer
ATOL	Long	FB	aa ... 00		0	Convert ASCII to long Store in A
LTOA	Long	FC	ff			Convert long to ASCII Store in string buffer
FSTATUS	Float	FD		ss		Get floating point status of A
XOP		FE				Extended opcode prefix (extended opcodes are listed below)
NOP		FF				No Operation
FUNCTION		FE0n FE1n FE2n FE3n			0	User defined functions 0-15 User defined functions 16-31 User defined functions 32-47 User defined functions 48-63
IF_FSTATUSA	Float	FE80	ss			Execute user function code if FSTATUSA conditions match
IF_FSTATUSB	Float	FE81	ss			Execute user function code if FSTATUSB conditions match
IF_FCOMPARE	Float	FE82	ss			Execute user function code if FCOMPARE conditions match
IF_LSTATUSA	Long	FE83	ss			Execute user function code if LSTATUSA conditions match
IF_LSTATUSB	Long	FE84	ss			Execute user function code if LSTATUSB conditions match
IF_LCOMPARE	Long	FE85	ss			Execute user function code if LCOMPARE conditions match
IF_LUCOMPARE	Long	FE86	ss			Execute user function code if LUCOMPARE conditions match
IF_LTST	Long	FE87	ss			Execute user function code if LTST conditions match
TABLE	Either	FE88				Table Lookup (user function)
POLY	Float	FE89				Calculate n th degree polynomial (user function)
READBYTE	Long	FE90		bb		Get lower 8 bits of register A
READWORD	Long	FE91		bb		Get lower 16 bits of register A
READLONG	Long	FE92		bb		Get long integer value of register A
READFLOAT	Float	FE93		bb		Get floating point value of register A
LINCA	Long	FE94				A = A + 1
LINCB	Long	FE95				B = B + 1
LDECA	Long	FE96				A = A - 1
LDECB	Long	FE97				B = B - 1
LAND	Long	FE98				A = A AND B
LOR	Long	FE99				A = A OR B
LXOR	Long	FE9A				A = A XOR B
LNOT	Long	FE9B				A = NOT A
LTST	Long	FE9C	ss			Get the status of A AND B
LSHIFT	Long	FE9D				A = A shifted by B bit positions
LWRITEA	Long	FEAx	yyyy zzzz			Write register and select A
LWRITEB	Long	FEBx	yyyy zzzz		x	Write register and select B
LREAD	Long	FECx		yyyy zzzz		Read register
LUDIV	Long	FEDx			x	A = A / B (unsigned long) Remainder stored in register 0
POWER	Float	FEE0				A = A ** B
ROOT	Float	FEE1				A = the Bth root of A
MIN	Float	FEE2				A = minimum of A and B
MAX	Float	FEE3				A = maximum of A and B

FRACTION	Float	FEE4			0	Load Register 0 with the fractional part of A
ASIN	Float	FEE5				A = asin(A) radians
ACOS	Float	FEE6				A = acos(A) radians
ATAN	Float	FEE7				A = atan(A) radians
ATAN2	Float	FEE8				A = atan(A/B)
LCOMPARE	Long	FEE9		ss		Compare A and B (signed long integer)
LUCOMPARE	Long	FEEA		ss		Compare A and B (unsigned long integer)
LSTATUS	Long	FEEB		ss		Get long status of A
LNEGATE	Long	FEEC				A = -A
LABS	Long	FEE D				A = A
LEFT		FEEE				Right parenthesis
RIGHT		FE EF			0	Left parenthesis
LOADZERO	Float	FE F0			0	Load Register 0 with Zero
LOADONE	Float	FE F1			0	Load Register 0 with 1.0
LOADE	Float	FE F2			0	Load Register 0 with e
LOADPI	Float	FE F3			0	Load Register 0 with pi
LONGBYTE	Long	FE F4	bb		0	Write signed byte to register 0 Convert to long
LONGUBYTE	Long	FE F5	bb		0	Write unsigned byte to register 0 Convert to long
LONGWORD	Long	FE F6	www w		0	Write signed word to register 0 Convert to long
LONGUWORD	Long	FE F7	www w		0	Write unsigned word to register 0 Convert to long
IEEEMODE		FE F8				Set IEEE mode (default)
PICMODE		FE F9				Set PIC mode
CHECKSUM		FE FA			0	Calculate checksum for uM-FPU code
BREAK		FE FB				Debug breakpoint
TRACEOFF		FE FC				Turn debug trace off
TRACEON		FE FD				Turn debug trace on
TRACESTR		FE FE	aa ... 00			Send debug string to trace buffer
VERSION		FE FF				Copy version string to string buffer

Notes:

Data Type	data type required by opcode
Opcode	hexadecimal opcode value
Arguments	additional data required by opcode
Returns	data returned by opcode
B Reg	value of B register after opcode executes
x	register number (0-15)
n	function number (0-63)
yyyy	most significant 16 bits of 32-bit value
zzzz	least significant 16 bits of 32-bit value
ss	status byte
bb	8-bit value
www w	16-bit value
aa ... 00	zero terminated ASCII string

Appendix B

Floating Point Numbers


Floating point numbers can store both very large and very small values by “floating” the window of precision to fit the scale of the number. Fixed point numbers can’t handle very large or very small numbers and are prone to loss of precision when numbers are divided. The representation of floating point numbers used by the uM-FPU is defined by the IEEE 754 standard.

The range of numbers that can be handled is approximately $\pm 10^{38.53}$.

IEEE 754 32-bit Floating Point Representation

IEEE floating point numbers have three components: the sign, the exponent, and the mantissa. The sign indicates whether the number is positive or negative. The exponent has an implied base of two. The mantissa is composed of the fraction.

The 32-bit IEEE 754 representation is as follows:



Sign Bit (S)

The sign bit is 0 for a positive number and 1 for a negative number.

Exponent

The exponent field is an 8-bit field that stores the value of the exponent with a bias of 127 that allows it to represent both positive and negative exponents. For example, if the exponent field is 128, it represents an exponent of one ($128 - 127 = 1$). An exponent field of all zeroes is used for denormalized numbers and an exponent field of all ones is used for the special numbers +infinity, -infinity and Not-a-Number (described below).

Mantissa

The mantissa is a 23-bit field that stores the precision bits of the number. For normalized numbers there is an implied leading bit equal to one.

Special Values

Zero

A zero value is represented by an exponent of zero and a mantissa of zero. Note that +0 and -0 are distinct values although they compare as equal.

Denormalized

If an exponent is all zeros, but the mantissa is non-zero the value is a denormalized number. Denormalized numbers are used to represent very small numbers and provide for an extended range and a graceful transition towards zero on underflows. Note: The uM-FPU does not support operations using denormalized numbers.

Infinity

The values +infinity and –infinity are denoted with an exponent of all ones and a fraction of all zeroes. The sign bit distinguishes between +infinity and –infinity. This allows operations to continue past an overflow. A nonzero number divided by zero will result in an infinity value.

Not A Number (NaN)

The value NaN is used to represent a value that does not represent a real number. An operation such as zero divided by zero will result in a value of NaN. The NaN value will flow through any mathematical operation. Note: The uM-FPU initializes all of its registers to NaN at reset, therefore any operation that uses a register that has not been previously set with a value will produce a result of NaN.

Some examples of IEEE 754 32-bit floating point values displayed as PicBasic data constants are as follows:

```

DATA $00, $00, $00, $00      '0.0
DATA $3D, $CC, $CC, $CD      '0.1
DATA $3F, $00, $00, $00      '0.5
DATA $3F, $40, $00, $00      '0.75
DATA $3F, $7F, $F9, $72      '0.9999
DATA $3F, $80, $00, $00      '1.0
DATA $40, $00, $00, $00      '2.0
DATA $40, $2D, $F8, $54      '2.7182818 (e)
DATA $40, $49, $0F, $DB      '3.1415927 (pi)
DATA $41, $20, $00, $00      '10.0
DATA $42, $C8, $00, $00      '100.0
DATA $44, $7A, $00, $00      '1000.0
DATA $44, $9A, $52, $2B      '1234.5678
DATA $49, $74, $24, $00      '1000000.0
DATA $80, $00, $00, $00      '-0.0
DATA $BF, $80, $00, $00      '-1.0
DATA $C1, $20, $00, $00      '-10.0
DATA $C2, $C8, $00, $00      '-100.0
DATA $7F, $C0, $00, $00      'NaN (Not-a-Number)
DATA $7F, $80, $00, $00      '+inf
DATA $FF, $80, $00, $00      '-inf

```